

# CR 400

**Shurtape®**  
TRUE TO YOUR WORK™

## PERFORMANCE GRADE FLATBACK PAPER PACKAGING TAPE

recyclable



passes WMU standard  
[www.wmich.edu/pilotplants](http://www.wmich.edu/pilotplants)

### TYPICAL APPLICATIONS

- For hand and machine carton sealing
- Also used for splicing various substrates
- Can also be used for general purpose packaging, binding, holding, tabbing, reinforcing, banding and patching applications

### PRODUCT FEATURES

- Curbside recyclable (recycles on the box)
- Very high adhesion
- Excellent quick stick and holding power
- High cross-directional strength
- Resistant to curling, abrasion and water
- Strong, flexible and conformable kraft backing that blends well with kraft cartons
- Meets FDA specifications for indirect food contact

### CONSTRUCTION

Overall Grade/Function: General Purpose

Backing: FSC Certified, extensible, kraft, flatback paper

Adhesive: Synthetic rubber-based

### STANDARD WIDTH(S)

48 mm 72 mm

### STANDARD LENGTH(S)

55 m 548 m

Contact your Shurtape sales representative for other available sizes

### STANDARD CORE SIZE

3 in

### APPLICABLE STANDARDS

ASTM D 6123/D 6123M-07 (2012), Type II; FDA Indirect Contact

CFR 21 - 174.5, 175.105, 176.170 & 176.180

### COLOR(S)



### PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	35 lbs/in width	61.3 N/10 mm
Adhesion to Stainless Steel	110 oz/in width	12.04 N/10 mm
Thickness	6.0 mils	0.15 mm
Elongation	6%	6%
Service Temperature Range	60 F to 150 F	16 C to 66 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

### STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment.

Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

